PRODUCT DATA SHEET

Quartz-Based Primer

codex Casa Fluente

White, filled primer for codex wall treatments

Description:

codex Casa Fluente is a high quality, white, filled primer for wall and ceiling surfaces. codex Casa Fluente can be used for all decorative trowel and brush techniques with mineral smoothing compounds and renders in both interior and exterior locations. Especially for substrate preparation for codex Palazzo Colore and codex Villa Rustica. codex Casa Fluente improves adhesion and makes it easier to apply an even and consistent coat.

Suitable for / on:

- wall and ceiling surfaces
- damp areas, bathrooms
- indoor pool areas
- lime-, lime-cement- and gypsum-renders
- plasterboard and plaster-fibreboard
- system component of codex Casa Mia

Product Properties / Benefits:

codex Casa Fluente is a hard-elastic, water-repellent, rapid-drying, filled primer with excellent adhesion properties. codex Casa Fluente has good coverage and is water vapour permeable.

- Good coverage
- Suitable for damp areas
- Rapid drying
- Diffusive
- Can be thinned with water
- Interior and exterior use

Technical Data:

Packaging:	plastic drum
Packsize:	5 kg
Shelf life:	12 months
Colour:	white
Consumption:	100 – 150 g/m²

Application conditions:

Temperature:	8 °C to 30 °C / 46 °F to 86 °F
Relative humidity:	30 % RH – 75 % RH

codex | A Brand of UFLOOR Systems

D | Uzin Utz AG | Dieselstraße 3 | D-89079 Ulm | Telefon + 49 (0)731 4097-0 | Telefax + 49 (0)731 4097-214 | E-Mail info@codex-x.com | Internet www.codex-x.com

GB | Uzin Ltd. | 4/5 Cholswell Court | Shippon | Abingdon | Oxon OX13 6HX | Telephone + 44 (0)12 35 53 41-06 | Telefax + 44 (0)12 35 53 41-07 | E-mail info@codex-x.co.uk | Internet www.codex-x.co.uk

Substrate Preparation:

The substrate must be flat, sound, dry, free from cracks, clean and free from materials that would impair adhesion. Test the substrate in accordance with applicable standards and notices and report any deficiencies. Remove any areas that are weakly bonded or not load bearing, e.g. by brushing, abrading or grinding, etc. Smooth over any imperfections, damage, grooves, etc. with suitable codex smoothing compounds. On problem surfaces, incorporate a fine-mesh sheet webbing during preparation. Remove any residues of soiling, e.g. from soot, tar, grease using suitable treatments. Dry-wall constructions must be thoroughly primed with codex Fliesengrund and then prepared with codex Casa Plana and a fine-mesh sheet webbing.

Refer to the Product Data Sheets for other codex products used.

Application:

1. On very absorbent surfaces, prime with codex Fliesengrund.
2. Before use, thoroughly stir codex Casa Fluente and then apply with a paint brush or similar using cross-strokes.
3. Clean tools with water after use.

Consumption:

	Consumption:	Coverage per 5 kg-container:
codex Casa Fluente	100 – 150 g/m²	approx. 40 m²

Important Notes:

- Shelf life minimum 12 months in original packaging when stored in cool, dry and frost-free conditions. Carefully and tightly reseal opened containers and use the contents as quickly as possible.
- During application and drying, substrate and air temperature should be between 8 °C and 30 °C / 46 °F and 86 °F and the relative humidity should be between 30 % and 75 %.
- Do not use in underwater locations.
- Due to the "individual handwriting", sample surfaces on project work that will later be carried out over the entire surface, must be completed personally by the installer.
- The unique appearance and the special effects of the decoratively designed surfaces will, in the first instance, be produced with the influence of light. To evoke the effect in each respective area, we recommend to the installer that he should present the technique to the customer by means of sample boards in the desired colours and in the proposed area. Only in this way can "light and effects" be assessed and a false impression be avoided.

Protection of the Workplace and the Environment:

Solvent-free. Non-flammable. Requires no special protection or precautions in general use. Use of barrier cream and ventilation of the work area are recommended.

Disposal:

Where possible, collect all product waste and re-use. Do not allow dispersal into drains, sewers or ground. Empty, scraped and drip-free plastic containers are recyclable. Containers with liquid residues, as well as the liquid product, are classed as Special Waste. Dried product residues are classed as Construction Waste.

The above information is based on our experience and careful investigations. The variety of associated materials and different construction and working conditions cannot be individually checked or influenced by us. The quality of your work depends, therefore, on your own professional judgement and product usage. If in doubt, conduct a small test or obtain technical advice. Observe the installation recommendations of the covering manufacturer. The publication of this Product Data Sheet invalidates all previous Product Information.

03.07 | 03.07 | 0.000 | Mar