

Textured Finish

codex Villa Rustica

Ready to use, textured fine finish for use with decorative glaze techniques

Description:

codex Villa Rustica is a ready to use, filled, textured render for creating decorative wall and ceiling finishes. Suitable for use as a top-coat or as a base for glazes. With codex Villa Rustica, high-class and individual surface finishes can be produced in the Mediterranean style in a range of different colours. Using different application techniques and different numbers of coats of the codex Villa Colore glaze, individual surface effects can be achieved. For interior and exterior use.

Suitable for/on:

- ▶ presentation areas, such as e.g. entrance halls, restaurants, banks, etc.
- ▶ living areas
- ▶ cement-, lime-cement- and gypsum-renders
- ▶ concrete
- ▶ plasterboard and plaster-fibreboard
- ▶ tiling boards, hard-foam boards
- ▶ sound coatings
- ▶ sound coats of old paint



Product Properties / Benefits:

codex Villa Rustica is a ready to use, mineral-filled, fine textured render. Small holes /air-holes in the substrate can be covered without pre-filling. codex Villa Rustica has excellent covering power and is water vapour permeable.

- ▶ Good covering power
- ▶ Suitable for damp areas
- ▶ Rapid drying
- ▶ Vapour permeable
- ▶ Mould resistant
- ▶ Interior and exterior use

Technical Data:

Packaging:	plastic drum
Packsize:	8 kg
Shelf life:	12 months
Colour:	white
Consumption:	approx.. 250 g/m ²

Application Conditions:

Temperature:	8 °C to 30 °C / 46 °F to 86 °F
Relative humidity:	30 % RH to 75 % RH

Substrate Preparation:

The substrate must be flat, sound, dry, free from cracks, clean and free from materials that would impair adhesion. Test the substrate in accordance with applicable standards and notices and report any deficiencies. Remove any areas that are weakly bonded or not load bearing, e.g. by brushing, abrading or grinding, etc. Smooth over any imperfections, damage, grooves, etc. with suitable codex smoothing compounds. On problem surfaces, incorporate a fine-mesh sheet webbing during preparation. Remove any residues of soiling, e.g. from soot, tar, grease using suitable treatments. Dry-wall constructions must be thoroughly primed with codex Fliesengrund and then prepared with codex Casa Plana and a fine-mesh sheet webbing.

Refer to the Product Data Sheets for other codex products used.

Application:

1. Coat the prepared substrate with codex Casa Fluente using cross-strokes with either a brush or a roller.
2. Before the start of work, stir the codex Villa Rustica well and then apply with a roller – whilst still fresh, create the desired texture using a brush. To achieve a heavier texture, a second coat can be applied after a drying time of approx. 2 hours.
3. Once the codex Villa Rustica is dry, the surface can be finished with the coloured glaze, codex Villa Colore.
4. Clean tools with water after use.

Consumption:

codex Villa Rustica	250 g/m ² per coat
---------------------	-------------------------------

Important Notes:

- ▶ Shelf life minimum 12 months in original packaging when stored in cool, dry and frost-free conditions. Carefully and tightly reseal opened containers and use the contents as quickly as possible.
- ▶ Do not use on surfaces that are in permanently wet areas or are exposed to direct spray-water.
- ▶ During application and drying, substrate and air temperature should be between 8 °C and 30 °C / 46 °F and 86 °F and the relative humidity should be between 30% and 75%.
- ▶ Due to the "individual handwriting", sample surfaces on project work that will later be carried out over the entire surface, must be completed personally by the installer.
- ▶ The unique appearance and the special effects of the decoratively designed surfaces will, in the first instance, be produced with the influence of light. To evoke the effect in each respective area, we recommend to the installer that he should present the technique to the customer by means of sample boards in the desired colours and in the proposed area. Only in this way can "light and effects" be assessed and a false impression be avoided.

Protection of the Workplace and the Environment:

Solvent-free. Non-flammable. Requires no special protection or precautions in general use. Use of barrier cream and ventilation of the work area are recommended.

Disposal:

Where possible, collect all product waste and re-use. Do not allow dispersal into drains, sewers or ground. Empty, scraped and drip-free plastic containers are recyclable. Containers with liquid residue, as well as the liquid product, are classed as Special Waste. Dried product residues are classed as Construction Waste.